



FAP Srl

Via G.Verga, 5 | 20842 Besana Brianza (MB) | Italy
tel. +39 0362 994943 | fax +39 0362 942256 | www.fapitaly.com | info@fapitaly.com



TECHNICAL DATA – EXTRUSION LINE EXT 753

01 GENERAL INFORMATION

FAP's extrusion line EXT 753 produces **polyethylene (PE)** and **polypropylene (PP)** expanded film using "Direct Gasing" extrusion technology that can be used in all production fields where it is necessary to insulate, package, protect (for example in building, electric and electronic, mechanical, automotive, food industries, packaging).

| | |
|--|---|
| Raw materials | PE/PP granule |
| Expansion agent | isobutane /normal butane gas |
| Foam's characteristic: | non cross-linked, 100% recyclable, flexible, innovative, technical, resistant, high-performance, does not emit toxins, does not cause allergic reactions, practical, universal. |
| Foam's density: | PE 16 : 150 kg/m ³ PP 35 : 150 kg/m ³ |
| Foam's widths: | PE 600 : 2500 mm PP 1000 : 1600 mm |
| 1 Kg of PE/PP composition: | 70 ÷ 95 % raw material of PE / PP, 5 ÷ 30% additives (stabilizers, nucleating, talc, colorants, gas, etc.) |
| Gas consumption: | 20 : 60 Kg/h |
| Power consumption: | 200 Kw/h |
| Water consumption: | 170 liters/month |
| Max. production capacity | PE 160 : 400 kg/h PP 200 : 400 kg/h |
| Approximate production capacity | PE 60.000 m ³ /year PP 42.000 m ³ /year |

02 GOODS & SERVICES

- FAP offers full extrusion lines, machines for the treatment of granulated blends, extrusion gas controlling unit, gravimetric dosers units, equipment for the treatment of the film and winding units, additional equipment for foam conversion.
- Know-how: FAP provides the specific advanced knowledge of all production processes.
- FAP guarantees post-sale technical support for the successful management and maintenance, rapid supply of spare parts, immediate assistance for any kind of support, concerning production, development of the product scale, etc.
- Warranty for FAP machinery excluding wearing parts is 12 month from the delivery date (to be determined in contract).

MACHINERY STRUCTURE

| | | | | | | | | | |
|----------------------|---|------------|-------------------------|-------------|--------|---------------|-----------------|----------------------|------------------------|
| 01 | DOSERS Automatic feeder; High precision gravimetric doser unit with 5 stations; Dosers' support structure. | | | | | | | | |
| 02 | EXTRUDER's BODY Complete extruder EXT 753 with control tools for temperature and pressure. <table style="width: 100%; border: none;"> <tr> <td style="padding: 2px;">Extruder</td> <td style="padding: 2px;">Twin Screw Extruder 753</td> </tr> <tr> <td style="padding: 2px;">Motor Power</td> <td style="padding: 2px;">Kw 104</td> </tr> <tr> <td style="padding: 2px;">Heating Power</td> <td style="padding: 2px;">Kw 150</td> </tr> <tr> <td style="padding: 2px;">Tot. Installed Power</td> <td style="padding: 2px;">Kw 280 (only Extruder)</td> </tr> </table> | Extruder | Twin Screw Extruder 753 | Motor Power | Kw 104 | Heating Power | Kw 150 | Tot. Installed Power | Kw 280 (only Extruder) |
| Extruder | Twin Screw Extruder 753 | | | | | | | | |
| Motor Power | Kw 104 | | | | | | | | |
| Heating Power | Kw 150 | | | | | | | | |
| Tot. Installed Power | Kw 280 (only Extruder) | | | | | | | | |
| 03 | EXTRUSION HEAD Extrusion Head for production of normal thickness foam (0,8:5 mm) Optional: - Extrusion Head for production of Big Thickness foam (5:20 mm) - Pipe Extrusion Head with associated and additional equipment* ; (* Water cooling units, Extraction and cutting of tubes; Manual winder for pipes; Extruder with the head for the lamination of the film to the outside of the tubes coverage.) | | | | | | | | |
| 04 | CALIBRATING UNITS FOR WIDTHS | | | | | | | | |
| 05 | GROUP FOR SUPPORT, DISTENSION AND COOLING OF FOAM | | | | | | | | |
| 05 | AUTOMATIC WINDER Two axis winder with automatic cutting and core glue system. Type AVV 22.2 LW <table style="width: 100%; border: none;"> <tr> <td style="padding: 2px;">Width film</td> <td style="padding: 2px;">2100 mm</td> </tr> <tr> <td style="padding: 2px;">Max. Weight</td> <td style="padding: 2px;">50 Kg</td> </tr> <tr> <td style="padding: 2px;">Speed</td> <td style="padding: 2px;">160 mt./minute'</td> </tr> </table> | Width film | 2100 mm | Max. Weight | 50 Kg | Speed | 160 mt./minute' | | |
| Width film | 2100 mm | | | | | | | | |
| Max. Weight | 50 Kg | | | | | | | | |
| Speed | 160 mt./minute' | | | | | | | | |
| 06 | HIGH PRESSURE GAS | | | | | | | | |
| 07 | WATER CHILLER (can be purchased by client) | | | | | | | | |
| 08 | MACHINERY TO COMPLETE PRODUCTION Cutting On-Line group with blades and aspirators; Laminator ON-LINE; Laminator OFF-LINE; Unwinder for laminator; Laminator for multilayer foam production; Cutting and welding machines for sheets and bags; Cutting machines for plates and angular protection formats; Punch machines and tubular welding. | | | | | | | | |

This document is the property of company **FAP Srl** and shall not be disclosed to third parties or reproduced without permission of **FAP Srl**. The contents are private and confidential. Copyright in this document and in other projects created by **FAP Srl** belongs to him. It is forbidden to reproduce or modify any kind of document or project, created by the company. All dates concerning production should be considered as approximate.

FAP S.R.L.