




FAP Srl

Via G.Verga, 5 | 20842 Besana Brianza (MB) | Italy
tel. +39 0362 994943 | fax +39 0362 942256 | www.fapitaly.com | info@fapitaly.com



TECHNICAL DATA – EXTRUSION LINE EXT 942

01 GENERAL INFORMATION

FAP's extrusion line EXT 942 produces **polyethylene (PE)** and **polypropylene (PP) expanded film** using "Direct Gasing" extrusion technology that can be used in all production fields where it is necessary to insulate, package, protect (for example in building, electric and electronic, mechanical, automotive, food industries, packaging).

Raw materials	PE/PP granule
Expansion agent	isobutane /normal butane gas
Foam's characteristic:	non cross-linked, 100% recyclable, flexible, innovative, technical, resistant, high-performance, does not emit toxins, does not cause allergic reactions, practical, universal.
Foam's density:	PE 18 : 150 kg/m ³ PP 30 : 200 kg/m ³
Foam's widths:	PE 1000 : 2500 mm PP 1000 : 2500 mm
1 Kg of PE/PP composition:	70 ÷ 95 % raw material of PE / PP, 5 ÷ 30% additives (stabilizers, nucleating, talc, colorants, gas, etc.)
Gas consumption:	30 : 120 Kg/h
Power consumption:	400 Kw/h
Water consumption:	300 liters/month
Max. production capacity	PE 240 : 700 kg/h PP 280 : 700 kg/h
Approximate production capacity	PE 124.550 m ³ /year PP 68.900 m ³ /year

02 GOODS & SERVICES

- FAP offers full extrusion lines, machines for the treatment of granulated blends, extrusion gas controlling unit, gravimetric dosers units, equipment for the treatment of the film and winding units, additional equipment for foam conversion.
- Know-how: FAP provides the specific advanced knowledge of all production processes.
- FAP guarantees post-sale technical support for the successful management and maintenance, rapid supply of spare parts, immediate assistance for any kind of support, concerning production, development of the product scale, etc.
- Warranty for FAP machinery excluding wearing parts is 12 month from the delivery date (to be determined in contract).

MACHINERY STRUCTURE

01	DOSERS Automatic feeder; High precision gravimetric doser unit with 5 stations; Dosers' support structure.								
02	EXTRUDER's BODY Complete extruder EXT 942 with control tools for temperature and pressure. <table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">Extruder</td> <td>Twin Screw Extruder 942</td> </tr> <tr> <td>Motor Power</td> <td>Kw 200</td> </tr> <tr> <td>Heating Power</td> <td>Kw 250</td> </tr> <tr> <td>Tot. Installed Power</td> <td>Kw 450 (only Extruder)</td> </tr> </table>	Extruder	Twin Screw Extruder 942	Motor Power	Kw 200	Heating Power	Kw 250	Tot. Installed Power	Kw 450 (only Extruder)
Extruder	Twin Screw Extruder 942								
Motor Power	Kw 200								
Heating Power	Kw 250								
Tot. Installed Power	Kw 450 (only Extruder)								
03	EXTRUSION HEAD Extrusion Head for production of normal thickness foam (1:5 mm) Optional: - Extrusion Head for production of Big Thickness foam (5:25 mm) - Pipe Extrusion Head with associated and additional equipment* ; (* Water cooling units, Extraction and cutting of tubes; Manual winder for pipes; Extruder with the head for the lamination of the film to the outside of the tubes coverage.)								
04	CALIBRATING UNITS FOR WIDTHS								
05	GROUP FOR SUPPORT, DISTENSION AND COOLING OF FOAM								
05	AUTOMATIC WINDER Two axis winder with automatic cutting and core glue system. Type AVV 27.2 LW (example) <table style="width: 100%; border: none;"> <tr> <td style="width: 50%;">Width film</td> <td>2550 mm</td> </tr> <tr> <td>Max. Weight</td> <td>60 Kg</td> </tr> <tr> <td>Speed</td> <td>160 mt./minute'</td> </tr> </table>	Width film	2550 mm	Max. Weight	60 Kg	Speed	160 mt./minute'		
Width film	2550 mm								
Max. Weight	60 Kg								
Speed	160 mt./minute'								
06	HIGH PRESSURE GAS								
07	WATER CHILLER (can be purchased by client)								
08	MACHINERY TO COMPLETE PRODUCTION Cutting On-Line group with blades and aspirators; Laminator ON-LINE; Laminator OFF-LINE; Unwinder for laminator; Laminator for multilayer foam production; Cutting and welding machines for sheets and bags; Cutting machines for plates and angular protection formats; Punch machines and tubular welding.								

This document is the property of company **FAP Srl** and shall not be disclosed to third parties or reproduced without permission of **FAP Srl**.
 The contents are private and confidential. Copyright in this document and in other projects created by **FAP Srl** belongs to him. It is forbidden to reproduce or modify any kind of document or project, created by the company. All dates concerning production should be considered as approximate.

FAP S.R.L.